



# BUBBLEBUSTER®

# SPIKED ROLLERS

10 2 2020

Our **BUBBLEBUSTER®** Spiked Roller has become the brand that most contractors prefer for spiking coatings. Our rollers with 12mm spike are for all types of high build and self-leveling floor coatings. Our 12mm Super Sharp rollers are for fast setting coatings. **BUBBLEBUSTER®** spiked rollers with 31 mm spikes are for spiking floor overlays in excess of 4mm thick.

**BUBBLEBUSTER®** Spiked Rollers are available in a multitude of widths and are sold as complete assemblies with frames in standard form. Replacement roller refills are available in all widths.

## 12MM SPIKED ROLLERS



- Used for deaerating epoxies and polyurethanes.
- The **BUBBLEBUSTER®** spiked roller is excellent for coatings thinner than 4mm thick.
- The bubble prevents the spike roller from penetrating too deep. This stops the roller from picking up the product and causing splatter.
- Best used for high build.

ROLLER ASSEMBLY		12MM SPIKE REFILL	
BB721100	100mm	BB721100R	100mm
BB721225	225mm	BB721225R	225mm
BB721300	300mm	BB721300R	300mm
BB721450	450mm	BB721450R	450mm
BB721600	600mm	BB721600R	600mm
BB721900	900mm	BB721900R	900mm

## 12MM SHARP SPIKE ROLLERS



- Used for deaerating epoxies and polyurethanes.
- The 12mm spike is excellent for coatings thinner than 1mm thick.
- The sharp spike is used to leave the smallest footprint in the coating, which prevents the roller from picking up the product and causing splatter.
- Ideal for fast setting coatings.

SHARP ROLLER ASSEMBLY		12MM SHARP SPIKE REFILL	
BB721100SS	100mm	BB721100SSR	100mm
BB721225SS	225mm	BB721225SSR	225mm
BB721300SS	300mm	BB721300SSR	300mm
BB721450SS	450mm	BB721450SSR	450mm
BB721600SS	600mm	BB721600SSR	600mm
BB721900SS	900mm	BB721900SSR	900mm

## 31MM SPIKED ROLLERS



- Used for deaerating epoxies and polyurethanes.
- The 31mm spiked roller is excellent for coatings thicker than 4mm thick.
- The bubble prevents the spike roller from penetrating too deep. This stops the roller from picking up the product and causing splatter.
- Best used for both high build as well as self-levelling screed.

ROLLER ASSEMBLY		31MM SPIKE REFILL	
BB731100	100mm	BB731100R	100mm
BB731225	225mm	BB731225R	225mm
BB731300	300mm	BB731300R	300mm
BB731450	450mm	BB731450R	450mm
BB731600	600mm	BB731600R	600mm